



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Calmet Industrial, S.A. de C.V.

***1^{era} Privada 4831, Col. Niño Artillero
Monterrey, Nuevo León, México. C.P. 64280***

*(Hereinafter called the Organization) and hereby declares that Organization is accredited
in accordance with the recognized International Standard:*

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the
operation of a laboratory quality management system
(as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Dimensional Inspection and Mechanical Testing
(As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen
President

Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
755 W. Big Beaver, Suite 1325
Troy, Michigan. 48084

Initial Accreditation Date:

February 11, 2011

Issue Date:

October 17, 2023

Expiration Date:

November 30, 2025

Accreditation No.:

45294

Certificate No.:

L23-761-1

*The validity of this certificate is maintained through ongoing assessments based on a
continuous accreditation cycle. The validity of this certificate should be
confirmed through the PJLA website: www.pjlab.com*



Certificate of Accreditation: Supplement

Calmet Industrial, S.A. de C.V.

1^{era} Privada 4831, Col. Niño Artillero
Monterrey, Nuevo León, México. C.P. 64280
Contact Name: Eliud Elizondo Phone: 818-351-0368

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Dimensional Inspection ^F	Fixtures and Parts	Measurement of Parts Geometrically Dimensioned and Tolerance (GD&T)	ASME Y14.5 Micro Vu Model: M411	X= 150 mm Y= 150 mm
Dimensional Inspection ^{FO}	Fixtures and Parts	Measurement of Parts Geometrically Dimensioned and Tolerance (GD&T)	ASME Y14.5 CMM:	X= 1 000 mm Y= 700 mm Z= 600 mm
			ASME Y14.5 3D Scanning	(Measurement Volume in mm ³) 45 Field-of-View: 45 x 38 x 30 75 Field-of-View: 74 x 62 x 45 100 Field-of-View: 120 x 100 x 60 250 Field-of-View: 260 x 215 x 140 500 Field-of-View: 480 x 400 x 250
			ASME Y14.5 Faro Arm	X= 3 000 mm Y= 3 000 mm Z= 3 000 mm
Mechanical ^{FO}	Security Valves	Pneumatic Test	NOM-093-SCFI	15 psi to 600 psi

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer^F would mean that the laboratory performs this testing at its fixed location.
2. The presence of a superscript FO means that the laboratory performs testing of the indicated parameter both at its fixed location and onsite at customer locations. Example: Outside Micrometer^{FO} would mean that the laboratory performs this testing at its fixed location and onsite at customer locations.
3. This is the primary site for all quality management system activities.